



# **Product Specification**

Dimension (mm):	150(W) × 65(D) × 110(H)
Weight:	450g
Filtration Flow Rate:	800 - 1500 ml/min (Pressure: 1 bar)*
Filtration Capacity:	1000 L* / 3 months
Working Pressure (min - max):	1 bar - 3 bar (100 kPa - 300 kPa)
Filter Cartridge Model:	FC68

\*Depends on in-coming water quality

"Do not use with water that is microbiologically unsafe or unknown quality without carrying out adequate disinfection before or after the filtering process. Individuals requiring water of special microbiological purify should follow the advice of their doctor or local health officials regardingthe use and the consumption of their tapwater and water filtered by Gurgle F68 Tap Filter"

How to store

Store in a cool place with room temperature below 30° C. Avoid exposure to direct sunlight.

Another Innovation by:

**ELO Living Pte Ltd** 

www.elomart.com

Made in China

A member of:









Your loved ones can now enjoy the goodness of clean filtered water daily for drinking, cooking and food preparation without the hassle of boiling. The F68 Gurgle Tap Filter is conveniently installed on your kitchen tap, and cartridge replacement is an ease as you can easily twist and change.

## **Exciting Features**



High-flow nozzle with maximum filtration flow rate of 1.5 litres/min



Clean and better tasting water with Proprietary Membrane technology and Carbon filter



Easy-Twist design that allows replacement cartridge to be easily removed and securely fastened



Adaptor Pack with 7 adaptors and accessories for fuss-free installation

### **Superior Filtration Technology**

#### Stage 1 : Sediment Pre-Filter

Blocks out rust and sediments

#### Stage 2: Activated Carbon Filter

- Removes chlorine and bad odour
- Improves taste of drinking water



### Stage 3: Ultrafiltration Hollow Fibre Membrane

- Proprietary membrane technology with superior performance that can filter up to 0.01 microns
- Removes turbidity, suspended solids and fine particles

### **Easy DIY Installation**

The new F68 Gurgle Tap Filter comes with 6 Quick Fit and 1 Universal tap adaptor, as well as additional accessories.

#### Tap with Outer Thread









Adaptor

Tap with Inner Thread









Tap with Insufficient or Irregular Thread





## Additional Accessories Rubber O-Rings

Attachment Tool







21.5 mm 18.5 mm 16.5 mm