

SPRING

Water Filtration Pitcher S38

Product Specifications:

Dimensions	275 (L) x 138 (W) x 275 (H)
Weight	820g
Water Temperature	Not exceeding 38°C
Filtered Water Capacity	1.2L
Cartridge Lifespan	150 L(Approximately 2 months)*
Average Filtration Flow Rate	320 mL/min
Filtration Cartridge Model	SC38

* Depending on in-coming water

NOTE: Do not use with water microbiologically unsafe or of unknown quality without carrying out adequate disinfection before or after filtering process. Individuals requiring water of special microbiological purity should follow the advice of their doctor or local health officials regarding the use and consumption of their tap water and water filtered by this product



Manufacturer:

Member
Water Quality Association

Certified By:

Intertek

A Member Of:

swa
SINGAPORE WATER ASSOCIATION

SPRING
Water Filtration Pitcher S38

Enhanced User Features

Filtration Technology



Feature 1: Digital Filter Lifespan Indicator

- Easy digital read-out
- Users are informed of when to replace cartridge

Feature 2: Instant Fill Lid

- Refill the pitcher easily by letting the downward pressure of the running tap depress the caption, to fill up the reservoir, for filtration to commence

Stage 1: Micro-Screen Filter

- Effectively blocks out rust and water contaminants
- Removes sediments to improve water quality

Stage 2: Ion Exchange Resin

- Soften water effectively for better absorption

Stage 3: Activated Carbon

- Reduces chlorine and bad odour present to enhance the taste of water for drinking and cooking



BPA-Free Plastic



Certified Effective Chlorine Removal



Improves Taste and Removes Odour